PHOSTREAT 242



PRODUCT DESCRIPTION

PHOSTREAT 242 is based on a synergistic blend of phosphates and specific polymers for dispersion and phosphate conditioning. It can be used for boilers of any pressure to precipitate calcium hardness as a mobile phosphate sludge which can be easily removed via blow down.

	Units	BCI Specifications	Test Methods
Appearance	-	Clear liquid	ASTM-E2680
Specific gravity	g/cm³	1.23	ASTM-D891
PH as supplied	-	6.2	ASTM-D1293

TREATMENT AND DOSAGE REQUIREMENTS

PHOSTREAT 242 is normally dosed so as to maintain 30-70 mg/l as a phosphate reserve in the boiler water. The optimum treatment level depends on a number of conditions including the boiler pressure and the chemical characteristics of the feed water and the actual dosage rate will be determined by SWTC.

PHOSTREAT 242 may be injected using a dosage pump, dosage pot to either the feed tank or boiler shell, as appropriate to the particular plant. In diluted or undiluted form.

PRODUCT BENEFITS

Effective scale inhibitor. May be dosed direct from drum. Simple monitoring procedures. Contains specific, highly effective, phosphate dispersant.

DISCLAIMER

Any sale by BCI, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed. Otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED. Each customer must determine the suitability of seller concerning a possible use of any product, service or design is intended, or should be construed to grant any license under any patent or other intellectual property right.

الصناعات الكيميائية الأساسية **BASIC CHEMICAL INDUSTRIES**



البريد الإلكتروني: Sales@bci.com.sa

الفرع الرئيسى