


CHEMTREAT 271A



PRODUCT DESCRIPTION

CHEMTREAT 271A is silicone based and is used for the prevention of foam in cooling water systems as well as wastewater plant. It may be safely used in food process industries where food grade antifoam is required.

	Units	BCI Specifications	Test Methods
Appearance	-	Pale yellow opaque liquid	ASTM-E2680
PH as supplied	-	7.0	ASTM-D1293
Specific gravity	g/cm ³	<1.0	ASTM-D891

TREATMENT AND DOSAGE REQUIREMENTS

CHEMTREAT 271A is normally maintained at a concentration between 50 ppm and 500 ppm in the recirculating water. SWTC will establish the concentration necessary for the particular operating conditions.

CHEMTREAT 271A may be diluted with water if desired and applied by means of a pump. More usually, it is applied intermittently and may be added to the cooling pond or process without dilution.

PRODUCT BENEFITS

Efficient foam prevention.

Low toxicity.

Liquid product for ease of addition.

DISCLAIMER

Any sale by BCI, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed. Otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED. Each customer must determine the suitability of seller concerning a possible use of any product, service or design is intended, or should be construed to grant any license under any patent or other intellectual property right.

الصناعات الكيمائية الأساسية
BASIC CHEMICAL INDUSTRIES

HEAD OFFICE

P.O Box 1053, Dammam 31431, Saudi Arabia
T: +966 13 821 7777 F: +966 13 847 26 48
Email: Sales@bci.com.sa



الفرع الرئيسي

ص ب ١٠٥٣، الدمام ٣١٤٣١، المملكة العربية السعودية
ت: +٩٦٦ ١٣ ٨٢١ ٧٧٧٧ ف: +٩٦٦ ١٣ ٨٤٧ ٢٦٤٨
البريد الإلكتروني: Sales@bci.com.sa